

# Panic and Emergency Exit Hardware

## ARRONE® AR8800 Single Panic Bolt

Touchbar Panic Hardware

### Application

- Suitable for single doors up to 2440mm height and 750 - 1000mm wide
- or second opening leaf of double door set with rebated meeting stiles - See AR8808
- Suitable for use in open public areas (in accordance with BS EN 1125:2008)

### Features

- Two or three-point locking options - AR8800-2 or AR8800-3
- Vertical pullman latches
- Grade 304 Stainless Steel main body cover and cross bar operator (SSS finish only)
- Steel internal main body an pullman mechanism
- Grade 304 Stainless Steel pullman latchbolts
- AR8800-3 supplied with Grade 304 Stainless Steel Anti-thrust locking main body latchbolt preventing leverage externally
- Aluminium vertical rod covers
- Zinc alloy pullman covers
- Two way follower action
- Fully reversible
- "Push Bar To Open" signage supplied

### Standards and certification



#### Quality and performance:

Successfully type tested to all the requirements of BS EN1125:2008

3	7	6	B	1	3	2	2	B	A
---	---	---	---	---	---	---	---	---	---



#### Fire safety:

Included in a successful fire test to BS EN1634 Part 1. For use on 30 minutes, 60 minutes and 120 minutes timber fire doors and 240 minutes steel doors.



**CE marked:** Certificate 1121-CPD-AAA5002



**Certifire approved product:** Certificate CF5180

#### CPR Declaration of Performance Certificate - HUK0036

Available for Download - Go to [www.hoppe.co.uk/service/dop-certificates](http://www.hoppe.co.uk/service/dop-certificates)

### Finishes

- Satin Stainless Steel, Silver

